



|| XTR Rivet

Part #RF022

Physical Specifications

Tag Dimensions	155 L x 37 W x 6 H (mm) (6.1 L x 1.5 W x 0.2 H (inches))
Encapsulation	One piece no welding construction
Mounting Hole Diameter	5.3 mm (0.21 inches)
Weight	31 grams (0.068 lbs)
Packaging	300 tags per box
Attachment Method	2 rivets or screws
Resin	Polypropylene

RF Specifications

RF Protocol	UHF, EPC Class 1 Gen 2, ISO 18000-6C
IC Type	Impinj Monza 4D
User Memory	32 bit
EPC Memory	128 bit
Operating Frequency	860 - 960 MHz (Global)
Read Range (Typical)	7.6 Meters (25 Feet)
Write Distance (Typical)	2.44 Meters (8 Feet)

Environmental Specifications

Operational Temperature	-40C to 85C (-40F to 185F)
Application Temperature	-40C to 160C (-40F to 320F)
Mounting Substrates	Non-metallic surfaces
UV Stabilization	10 Years
Chemical Resistance	Water, Motor Oil, Hydraulic Oil, Dishwashing Detergent, Windex, Gasoline, Isopropyl Alcohol, Mineral Spirits, Acetone, Bleach, 409 Cleaner or Fantastic All Purpose Cleaner, Methyl Ethyl Ketone (MEK), Machine Oil

Environmental and Performance Testing*

Ingress Protection (IP) Rating	IP69K
Thermal Shock I In Accordance with IEC 60068-2-14 Test Nb	-20C to 85C (-4F to 185F)
Thermal Shock II In Accordance with IEC 60068-2-14 Test Na	-40C to 70C (-40F to 158F)
Steel Ball Impact Test	1.8 kg ball drop from 1.52 meters 5 times (4 lb ball drop from 5 feet 5 times)

* Testing performed in an A2LA Accredited Laboratory

Available in black: Part #RF006

WHO WORKS IN FRIGID WEATHER? WE DO, AND LOVE IT.



|| XTR Rivet

If your product or equipment must ship in the most frigid temperatures, you need assurance that the RFID tag will withstand the bitter cold. Xtreme RFID's XTR Rivet Tag continues working in temperatures as low as -40 degrees Celsius. Now that's frigid.

www.xtremerfid.com

 **XTREME RFID**
ready for anything