



|| XTR Cart

Part #RF031

Physical Specifications

Tag Dimensions	162 L x 25 W x 6 H (mm) (7.2 L x 0.85 W x 0.21 H (inches))
Encapsulation	One piece no welding construction
Mounting Hole Diameter	5.3 mm (0.21 inches)
Weight	25 grams (0.055 lbs)
Packaging	500 tags per box
Attachment Method	Snap in, 2 rivets or screws
Resin	Polypropylene

RF Specifications

RF Protocol	UHF, EPC Class 1 Gen 2, ISO 18000-6C
IC Type	Impinj Monza 5
User Memory	32 bit
EPC Memory	128 bit
Operating Frequency	860 - 960 MHz (Global)
Read Range (Typical)	7.6 Meters (25 Feet)
Write Distance (Typical)	2.44 Meters (8 Feet)

Environmental Specifications

Operational Temperature	-40C to 85C (-40F to 185F)
Application Temperature	-40C to 160C (-40F to 320F)
Mounting Substrates	Non-metallic surfaces
UV Stabilization	10 Years
Chemical Resistance	Water, Motor Oil, Hydraulic Oil, Dishwashing Detergent, Windex, Gasoline, Isopropyl Alcohol, Mineral Spirits, Acetone, Bleach, 409 Cleaner or Fantastic All Purpose Cleaner, Methyl Ethyl Ketone (MEK), Machine Oil

Environmental and Performance Testing*

Ingress Protection (IP) Rating	IP69K
Thermal Shock I In Accordance with IEC 60068-2-14 Test Nb	-20C to 85C (-4F to 185F)
Thermal Shock II In Accordance with IEC 60068-2-14 Test Na	-40C to 70C (-40F to 158F)
Steel Ball Impact Test	1.8 kg ball drop from 1.52 meters 5 times (4 lb ball drop from 5 feet 5 times)

* Testing performed in an A2LA Accredited Laboratory

**10 THOUSAND BRICKS.
10 BELOW ZERO.
NO SWEAT.**



IXTR Cart

When you work in extreme conditions—you need Xtreme tracking. Whether you're working in the coldest or hottest temperatures, or traveling down the rockiest roads, the XTR Cart stays securely in place and tracks with precision. Fight extreme with Xtreme—we're ready!

www.xtremerfid.com

 **XTREME RFID**
ready for anything